



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure DEHMR 5/7/8



Energy efficiency class

Selected product

- Article no.: 6102300003
- EAN code: 7630029408896
- Type: DEHMR5c
- Product category: Range hood
- Standard width: 55 cm
- Front design: ChromeClass
- Installation method: Integrated range hood



DEHMR 5/7/8

Additional settings

- Clean air function

Compliant to regulation

- (EU) Nr. 65/2014

Design

- Type: DEHMR5c
- Product category: Range hood
- Standard width: 55 cm
- Front design: ChromeClass
- Installation method: Integrated range hood

Dimensions

- Niche width: 520 mm
- Max. niche width: 520 mm
- Niche depth: 300 mm
- Appliance height: 330 mm
- Front height: 330 mm
- Appliance width: 520 mm
- Appliance depth: 300 mm
- Max. appliance depth: 300 mm
- Empty weight: 7 kg

Display and operation

- Controls: Touch keys
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Measurement and Calculation Method: EN 61591
- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: B
- Annual energy consumption: 66.5 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 24.9
- Fluid dynamic efficiency rating: B
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 1 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.27 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- Hood design: Fan module
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Dimming lights: 2-stage
- Grease filter: 1
- Side exhaust
- Non-return flap, integrated/attached: Included



Functions

- Extracted air
- Dimming lights: 2-stage
- Grease filter cleaning indicator
- Side exhaust
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time

Additional data

- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 90.9
- Illumination on cooking surface: 200 lux
- Grease absorption capacity rating: C
- Extracted air output, intensive setting: 640 m³/h
- Extracted air output, max. setting: 540 m³/h
- Extracted air output, min. setting: 270 m³/h
- Recirculation air output, intensive setting: 280 m³/h
- Recirculation air output, max. setting: 270 m³/h
- Recirculation air output, min. setting: 230 m³/h
- Extracted air noise output, intensive setting: 71 dB(A)
- Extracted air noise level, max. setting: 69 dB(A)
- Extracted air noise output, min. setting: 55 dB(A)
- Recirculation air noise output, intensive setting: 69 dB(A)
- Schalleistung Umluft max. Stufe: 68 dB(A)
- Recirculation air noise output, min. setting: 66 dB(A)
- Motor(s): 1
- Motor output: 265 W
- Feature level: 3

Service and interfaces

- Warranty: 2 years