



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure DFN



Energy efficiency class

Selected product

- Article no.: 6102700003 + 1029583
- EAN code: 7630029417331 + 7630029421925
- Type: DFN6c
- Product category: Range hood
- Standard width: 60 cm
- Front design: ChromeClass
- Installation method: Built-in range hood
- Recirculation air filter: Long-life activated charcoal filter



DFN

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: DFN6c
- Product category: Range hood
- Standard width: 60 cm
- Front design: ChromeClass
- Installation method: Built-in range hood
- Recirculation air filter: Long-life activated charcoal filter

Dimensions

- Depth with pull-out: 457.0 mm
- Niche width: 600 mm
- Max. niche width: 600 mm
- Niche depth: 305 mm
- Appliance height: 396 mm
- Front height: 40 mm
- Appliance width: 598 mm
- Appliance depth: 302 mm
- Max. appliance depth: 302 mm
- Empty weight: 12.5 kg

Display and operation

- Controls: Button
- Lighting: LED
- Number of lights: 2

Energy

- Measurement and Calculation Method: EN 61591
- Consumption when off: 0 W
- Light source regulations
- Energy efficiency class: A
- Annual energy consumption: 39.7 kWh
- Lighting efficiency rating: E
- Fluid dynamic efficiency: 33.5
- Fluid dynamic efficiency rating: E
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 1 x 6 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.21 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Connection cable: 1.5 m

Range hood features

- Hood design: Flatdesign
- Power levels: 3
- Grease filter: 2
- Non-return flap, integrated/attached: Included

Functions

- Recirculation air

**Additional data**

- Light colour in kelvin: 2800 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 9
- Illumination on cooking surface: 54 lux
- Grease absorption capacity rating: D
- Extracted air output, max. setting: 647 m³/h
- Extracted air output, min. setting: 256 m³/h
- Recirculation air output, max. setting: 490 m³/h
- Recirculation air output, min. setting: 205 m³/h
- Extracted air noise level, max. setting: 67 dB(A)
- Extracted air noise output, min. setting: 46 dB(A)
- Schalleistung Umluft max. Stufe: 73 dB(A)
- Recirculation air noise output, min. setting: 51 dB(A)
- Motor(s): 1
- Motor output: 200 W
- Feature level: 2

Service and interfaces

- Warranty: 2 years