



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

## Brochure DFSE



Energy efficiency class

### Selected product

- Article no.: 6102800000 + 1029582
- EAN code: 7630029417348 + 7630029421918
- Type: DFSE5
- Product category: Range hood
- Standard width: 55 cm
- Front design: Nero
- Installation method: Built-in range hood
- Recirculation air filter: Standard activated charcoal filter



## DFSE

### Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

### Design

- Type: DFSE5
- Product category: Range hood
- Standard width: 55 cm
- Front design: Nero
- Installation method: Built-in range hood
- Recirculation air filter: Standard activated charcoal filter

### Dimensions

- Depth with pull-out: 457.0 mm
- Niche width: 550 mm
- Max. niche width: 550 mm
- Niche depth: 305 mm
- Appliance height: 396 mm
- Front height: 40 mm
- Appliance width: 548 mm
- Appliance depth: 302 mm
- Max. appliance depth: 302 mm
- Empty weight: 12.5 kg

### Display and operation

- Controls: Touch keys
- Fan power level display
- Lighting: LED
- Number of lights: 2

### Energy

- Measurement and Calculation Method: EN 61591
- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: A
- Annual energy consumption: 43.4 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 31.9
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 1 x 5 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.2 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Connection cable: 1.5 m

### Range hood features

- Grease filter cleaning indicator
- Hood design: Flatdesign
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Grease filter: 2
- Non-return flap, integrated/attached: Included

### Functions

- Grease filter cleaning indicator
- Recirculation air
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time



#### **Additional data**

- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 76.1
- Illumination on cooking surface: 381 lux
- Grease absorption capacity rating: C
- Extracted air output, intensive setting: 625 m<sup>3</sup>/h
- Extracted air output, max. setting: 515 m<sup>3</sup>/h
- Extracted air output, min. setting: 240 m<sup>3</sup>/h
- Recirculation air output, intensive setting: 490 m<sup>3</sup>/h
- Recirculation air output, max. setting: 448 m<sup>3</sup>/h
- Recirculation air output, min. setting: 205 m<sup>3</sup>/h
- Extracted air noise output, intensive setting: 67 dB(A)
- Extracted air noise level, max. setting: 63 dB(A)
- Extracted air noise output, min. setting: 46 dB(A)
- Recirculation air noise output, intensive setting: 71 dB(A)
- Schalleistung Umluft max. Stufe: 69 dB(A)
- Recirculation air noise output, min. setting: 52 dB(A)
- Motor(s): 1
- Motor output: 200 W
- Feature level: 3

#### **Service and interfaces**

- Warranty: 2 years