



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure DF-SG 5/6



Energy efficiency class

Selected product

- Article no.: 6103000003 + 1029585
- EAN code: 7630029417409 + 7630029421949
- Type: DFSG5c
- Product category: Range hood
- With pullout glass
- Standard width: 55 cm
- Front design: ChromeClass
- Installation method: Built-in range hood
- Recirculation air filter: Long-life activated carbon filter plus



DF-SG 5/6

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: DFSG5c
- Product category: Range hood
- With pullout glass
- Standard width: 55 cm
- Front design: ChromeClass
- Installation method: Built-in range hood
- Recirculation air filter: Long-life activated carbon filter plus

Dimensions

- Depth with pull-out: 520.0 mm
- Niche width: 550 mm
- Max. niche width: 550 mm
- Niche depth: 280 mm
- Appliance height: 400 mm
- Front height: 46 mm
- Appliance width: 548 mm
- Appliance depth: 290 mm
- Max. appliance depth: 350 mm
- Empty weight: 16 kg

Display and operation

- Controls: Touch keys
- Fan power level display
- Lighting: LED
- Number of lights: 1

Energy

- Measurement and Calculation Method: EN 61591
- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: A
- Annual energy consumption: 44.9 kWh
- Lighting efficiency rating: C
- Fluid dynamic efficiency: 30.4
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 1 x 7 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.21 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- Hood design: Flatdesign
- Activated charcoal filter saturation indicator
- With pullout glass
- Power levels: 3 + i
- Grease filter: 1
- Non-return flap, integrated/attached: Included

Functions

- Grease filter cleaning indicator
- Recirculation air
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time



Additional data

- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 17
- Illumination on cooking surface: 119 lux
- Grease absorption capacity rating: D
- Extracted air output, intensive setting: 625 m³/h
- Extracted air output, max. setting: 537 m³/h
- Extracted air output, min. setting: 240 m³/h
- Recirculation air output, intensive setting: 384 m³/h
- Recirculation air output, max. setting: 368 m³/h
- Recirculation air output, min. setting: 165 m³/h
- Extracted air noise output, intensive setting: 66 dB(A)
- Extracted air noise level, max. setting: 63 dB(A)
- Extracted air noise output, min. setting: 46 dB(A)
- Recirculation air noise output, intensive setting: 70 dB(A)
- Schalleistung Umluft max. Stufe: 68 dB(A)
- Recirculation air noise output, min. setting: 51 dB(A)
- Motor(s): 1
- Motor output: 200 W
- Feature level: 3

Service and interfaces

- Warranty: 2 years