



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure DKS



Energy efficiency class

Selected product

- Article no.: 6104400001
- EAN code: 7630029426678
- Type: DKS5iw
- Product category: Range hood
- Standard width: 60 cm
- Front design: White
- Installation method: Built-in range hood



DKS

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: DKS5iw
- Product category: Range hood
- Standard width: 60 cm
- Front design: White
- Installation method: Built-in range hood

Dimensions

- Depth with pull-out: 464.0 mm
- Niche width: 600 mm
- Max. niche width: 600 mm
- Niche depth: 330 mm
- Appliance height: 282 mm
- Appliance width: 597 mm
- Appliance depth: 290 mm
- Max. appliance depth: 340 mm
- Empty weight: 11.5 kg

Display and operation

- Controls: slide switch
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Measurement and Calculation Method: EN 61591
- Consumption when off: 0 W
- Light source regulations
- Energy efficiency class: D
- Annual energy consumption: 60.5 kWh
- Lighting efficiency rating: E
- Fluid dynamic efficiency: 9.3
- Fluid dynamic efficiency rating: E
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 4 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.13 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Connection cable: 1.2 m

Range hood features

- Hood design: Pull-out hood
- Power levels: 3
- Grease filter: 1
- Non-return flap, integrated/attached: Integrated

Functions

- Extracted air

**Additional data**

- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 11
- Illumination on cooking surface: 90 lux
- Grease absorption capacity rating: B
- Extracted air output, max. setting: 394 m³/h
- Extracted air output, min. setting: 249 m³/h
- Recirculation air output, max. setting: 105 m³/h
- Recirculation air output, min. setting: 90 m³/h
- Extracted air noise level, max. setting: 65 dB(A)
- Extracted air noise output, min. setting: 53 dB(A)
- Schalleistung Umluft max. Stufe: 71 dB(A)
- Recirculation air noise output, min. setting: 68 dB(A)
- Motor output: 125 W
- Feature level: 1

Service and interfaces

- Warranty: 2 years