



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

## Brochure DWWE



Energy efficiency class

### Selected product

- Article no.: 6201700003 + 1046986
- EAN code: 7630029426722 + 7630029429020
- Type: DWE9c
- Product category: Range hood
- Standard width: 90 cm
- Front design: ChromeClass
- Installation method: Wall hood
- Recirculation air filter: Long-life activated charcoal filter



## DWE

### Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

### Design

- Type: DWE9c
- Product category: Range hood
- Standard width: 90 cm
- Front design: ChromeClass
- Installation method: Wall hood
- Recirculation air filter: Long-life activated charcoal filter

### Dimensions

- Device height exhaust air maximum: 810 mm
- Device height exhaust air: 650 mm
- Device height recirculation air: 710 mm
- Device height recirculation air maximum: 920 mm
- Front height: 60 mm
- Appliance width: 898 mm
- Appliance depth: 470 mm
- Max. appliance depth: 470 mm
- Empty weight: 22 kg

### Display and operation

- Controls: Touch keys
- Fan power level display
- Lighting: LED
- Number of lights: 2

### Energy

- Measurement and Calculation Method: EN 61591
- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: A+
- Annual energy consumption: 41.7 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 35
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 1 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.27 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Connection cable: 1.2 m

### Range hood features

- Grease filter cleaning indicator
- Hood design: cubic
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Dimming lights: 2-stage
- Grease filter: 3
- Non-return flap, integrated/attached: Included

### Functions

- OptiLink
- Dimming lights: 2-stage
- Grease filter cleaning indicator
- Recirculation air
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time



#### **Additional data**

- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 109
- Illumination on cooking surface: 240 lux
- Grease absorption capacity rating: C
- Extracted air output, intensive setting: 700 m<sup>3</sup>/h
- Extracted air output, max. setting: 580 m<sup>3</sup>/h
- Extracted air output, min. setting: 300 m<sup>3</sup>/h
- Recirculation air output, intensive setting: 440 m<sup>3</sup>/h
- Recirculation air output, max. setting: 420 m<sup>3</sup>/h
- Recirculation air output, min. setting: 280 m<sup>3</sup>/h
- Extracted air noise output, intensive setting: 69 dB(A)
- Extracted air noise level, max. setting: 66 dB(A)
- Extracted air noise output, min. setting: 52 dB(A)
- Recirculation air noise output, intensive setting: 76 dB(A)
- Schalleistung Umluft max. Stufe: 75 dB(A)
- Recirculation air noise output, min. setting: 69 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1
- Motor output: 270 W
- Feature level: 3

#### **Service and interfaces**

- Warranty: 2 years