

V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure DWQS



Selected appliance

- Article no.: 6201900003 + 1046987
- EAN code: 7630029426739 + 7630029429037
- Controls: push buttons
- Telescopic casing: Standard
- Standard width: 60.0 cm
- recirculation air
- Front design: ChromeClass
- Installation method: Wall hood
- Recirculation air filter: Standard activated charcoal filter

Details DWQS6

Design

- Controls: push buttons
- Telescopic casing: Standard
- Standard width: 60.0 cm
- recirculation air
- Front design: ChromeClass
- Installation method: Wall hood
- Recirculation air filter: Standard activated charcoal filter

Dimensions

- Device height exhaust air: 650 mm
- Device height exhaust air maximum: 810 mm
- Device height recirculation air: 710 mm
- Device height recirculation air maximum: 920 mm
- Front height: 60 mm
- Appliance width: 598 mm
- Appliance depth: 470 mm
- Max. appliance depth: 470 mm
- Empty weight: 15.6 kg

Display and operation

- Controls: push buttons
- Fan power level display
- Lighting: LED
- Number of lights: 2
- Grease filter cleaning indicator

Energy

- Energy efficiency rating: A+
- Annual energy consumption: 41.7 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 35
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240V~
- Nominal lighting output (quantity x W): 2 x 1 W W
- Frequency (1): 50Hz
- Connected loads (1): 0.27 kW
- Fuse protection (1): 10 A

- Plug type: CH Typ 12
- Connection cable: 1.2 m

Range hood features

- Extracted air noise level, max. setting: 66 dB(A)
- Telescopic casing: Standard
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Dimming lights
- Fleece grease filter: 2.0
- Non-return flap, integrated/attached: included

Functions

- Dimming lights
- Intensive setting
- Automatic after-running time

Additional data

- Recirculation air noise output, max. setting: 75 dB(A)
- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 109
- Illumination on cooking surface: 240 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 700 m³/h
- Extracted air output, max. setting: 580 m³/h
- Extracted air output, min. setting: 300 m³/h
- Recirculation air output, intensive setting: 440 m³/h
- Recirculation air output, max. setting: 420 m³/h
- Recirculation air output, min. setting: 280 m³/h
- Extracted air noise output, intensive setting: 69 dB(A)
- Extracted air noise level, max. setting: 66 dB(A)
- Extracted air noise output, min. setting: 52 dB(A)
- Recirculation air noise output, intensive setting: 76 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1.0
- Motor output: 270 W W
- Feature level: 4

Service and interfaces



- Warranty: 2 years