



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

## Brochure DFPQSL 6



### **Selected product**

- Article no.: 6103767002
- EAN code: 7630029427149
- Type: DFPQSL6g
- Product category: Range hood
- Standard width: 60 cm
- Front design: Black glass
- Installation method: Built-in range hood
- Recirculation air filter: Long-life activated charcoal filter



## DFPQSL 6

### Design

- Type: DFPQSL6g
- Product category: Range hood
- Standard width: 60 cm
- Front design: Black glass
- Installation method: Built-in range hood
- Recirculation air filter: Long-life activated charcoal filter

### Dimensions

- Niche width: 600 mm
- Max. niche width: 600 mm
- Niche depth: 330 mm
- Appliance height: 470 mm
- Front height: 25 mm
- Appliance width: 598 mm
- Appliance depth: 303 mm
- Max. appliance depth: 325 mm
- Empty weight: 21.8 kg

### Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

### Energy

- Measurement and Calculation Method: EN 61591
- Output - standby off: 0.48 W
- Consumption when off: 0 W
- Automatic shut-off consumption with network switched on: 0.5 W
- Energy efficiency class: A+
- Annual energy consumption: 24.6 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 35.4
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 2 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.23 kW
- Fuse protection (1): 10 A
- Plug type: CN CH1-10P
- Connection cable: 1.5 m

### Range hood features

- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- Selectable fan setting: Above steam filter
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Grease filter: 1
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: Included

### Functions

- ComfortFix
- Grease filter cleaning indicator
- Recirculation air
- Activated charcoal filter saturation indicator
- Cleaning lock
- Intensive setting
- Automatic after-running time

**Additional data**

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 28
- Illumination on cooking surface: 113 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 765 m<sup>3</sup>/h
- Extracted air output, max. setting: 602 m<sup>3</sup>/h
- Extracted air output, min. setting: 332 m<sup>3</sup>/h
- Recirculation air output, intensive setting: 635 m<sup>3</sup>/h
- Recirculation air output, max. setting: 551 m<sup>3</sup>/h
- Recirculation air output, min. setting: 270 m<sup>3</sup>/h
- Extracted air noise output, intensive setting: 70 dB(A)
- Extracted air noise level, max. setting: 70 dB(A)
- Extracted air noise output, min. setting: 49 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1
- Motor output: 230 W
- Feature level: 5