



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

## Brochure AiroClearWall V4000 with TwinBlower



### **Selected product**

- Article no.: 6202600003
- EAN code: 7630029434574
- Type: AW4T-62026
- Product category: Range hood
- Telescopic casing: Standard
- Standard width: 90 cm
- Front design: Black glass
- Installation method: Wall hood



## AiroClearWall V4000 with TwinBlower

### Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

### Design

- Type: AW4T-62026
- Product category: Range hood
- Telescopic casing: Standard
- Standard width: 90 cm
- Front design: Black glass
- Installation method: Wall hood

### Dimensions

- Device height exhaust air maximum: 1000 mm
- Device height exhaust air: 660 mm
- Front height: 55 mm
- Appliance width: 898 mm
- Appliance depth: 550 mm
- Max. appliance depth: 550 mm
- Empty weight: 46 kg

### Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

### Energy

- Measurement and Calculation Method: EN 61591
- Output - standby off: 0.4 W
- Consumption when off: 0 W
- Energy efficiency class: C
- Annual energy consumption: 159.1 kWh
- Lighting efficiency rating: B
- Fluid dynamic efficiency: 21.6
- Fluid dynamic efficiency rating: C
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 2 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.53 kW
- Fuse protection (1): 10 A
- Plug type: BS1363/10A
- Connection cable: 1.5 m

### Range hood features

- SilentPlus
- Activated charcoal filter saturation indicator
- Telescopic casing: Standard
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Grease filter: 3
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: Included

### Functions

- ComfortFix
- Extracted air
- Activated charcoal filter saturation indicator
- SilentPlus
- TwinBlower
- Cleaning lock
- Intensive setting
- Automatic after-running time

**Additional data**

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 200 mm
- Lighting efficiency: 25.5
- Illumination on cooking surface: 102 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 1262 m<sup>3</sup>/h
- Extracted air output, max. setting: 1164 m<sup>3</sup>/h
- Extracted air output, min. setting: 620 m<sup>3</sup>/h
- Extracted air noise output, intensive setting: 71 dB(A)
- Extracted air noise level, max. setting: 69 dB(A)
- Extracted air noise output, min. setting: 57 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 2
- Motor output: 530 W
- Feature level: 4

**Service and interfaces**

- Warranty: 2 years