



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure DWPQ



Selected product

- Article no.: 6202262002
- EAN code: 7630029427248
- Type: DWPQ9g
- Product category: Range hood
- Standard width: 90 cm
- Front design: Black glass
- Installation method: Wall hood



Details DW PQ9

Design

- Type: DWPQ9g
- Product category: Range hood
- Standard width: 90 cm
- Front design: Black glass
- Installation method: Wall hood

Dimensions

- Device height exhaust air: 460 mm
- Device height exhaust air maximum: 660 mm
- Device height recirculation air: 570 mm
- Device height recirculation air maximum: 770 mm
- Front height: 55 mm
- Appliance width: 898 mm
- Appliance depth: 550 mm
- Max. appliance depth: 550 mm
- Empty weight: 25.5 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Consumption when off: 0 W
- Energy efficiency rating: A+
- Annual energy consumption: 37.1 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 37.1
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240V~
- Nominal lighting output (quantity x W): 2 x 2 W
- Frequency (1): 50/60Hz
- Connected loads (1): 0.23 kW
- Fuse protection (1): 10 A
- Plug type: BS1363/13A
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Fleece grease filter: 3
- Non-return flap, integrated/attached: included

Functions

- Extracted air
- Grease filter cleaning indicator
- Intensive setting
- Automatic after-running time



Additional data

- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 33
- Illumination on cooking surface: 124 lux
- Grease absorption capacity rating: C
- Extracted air output, intensive setting: 880 m³/h
- Extracted air output, max. setting: 670 m³/h
- Extracted air output, min. setting: 340 m³/h
- Recirculation air output, intensive setting: 696 m³/h
- Recirculation air output, max. setting: 580 m³/h
- Recirculation air output, min. setting: 332 m³/h
- Extracted air noise output, intensive setting: 70 dB(A)
- Extracted air noise level, max. setting: 70 dB(A)
- Extracted air noise output, min. setting: 50 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1
- Motor output: 230 W
- Feature level: 5

Service and interfaces

- Warranty: 2 years