



# Data sheet AiroClearCabinet V4000

Article no.: V6400900001\_Abluft

Compliant to regulation (EU) Nr. 65/2014, (EU) Nr. 66/2014

Name	Unit	Value
Recirculation air noise output, min. setting	dB(A)	55
Schalleistung Umluft max. Stufe	dB(A)	66
Recirculation air noise output, intensive setting	dB(A)	68
ComfortFix		Yes
Consumption when off	W	0.0
(EU) Nr. 65/2014		Yes
(EU) Nr. 66/2014		Yes
Product category		Range hood
Annual energy consumption	kWh	43.9
Time increase factor		0.8
Fluid dynamic efficiency		33.1
Fluid dynamic efficiency rating		A
Energy efficiency index		46
Air output at best efficiency point	m <sup>3</sup> /h	348.60000000000025
Pressure capacity at best efficiency point	Pa	480
Extracted air output, min. setting	m <sup>3</sup> /h	309.0000000000002
Extracted air output, max. setting	m <sup>3</sup> /h	597.9999999999995
Extracted air output, intensive setting	m <sup>3</sup> /h	704.0000000000016
Electric power input at best efficiency point	W	140.3
Nominal lighting output (quantity x W)		2 x 2 W
Illumination on cooking surface	lx	169
Output - standby off	W	0.43
Extracted air noise output, min. setting	dB(A)	49
Extracted air noise level, max. setting	dB(A)	64
Extracted air noise output, intensive setting	dB(A)	67
Grease absorption capacity		78.0



Grease absorption capacity rating	C
Lighting efficiency	42.2
Lighting efficiency rating	A