



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure DFPQSL 9



Selected product

- Article no.: 6103868002
- EAN code: 7630029443736
- Product category: Range hood
- Telescopic casing: Standard
- Standard width: 90 cm
- Front design: Black glass
- Installation method: built-in range hood



Details DF PQSL9

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Product category: Range hood
- Telescopic casing: Standard
- Standard width: 90 cm
- Front design: Black glass
- Installation method: built-in range hood

Dimensions

- Depth with pull-out: 507.0 mm
- Niche width: 900 mm
- Max. niche width: 900 mm
- Niche depth: 330 mm
- Appliance height: 470 mm
- Front height: 25 mm
- Appliance width: 898 mm
- Appliance depth: 303 mm
- Max. appliance depth: 325 mm
- Empty weight: 27.1 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Consumption when off: 0.0 W
- Energy efficiency rating: A+
- Annual energy consumption: 31.2 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 34.7
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 2 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.13 kW
- Fuse protection (1): 10 A
- Plug type: SII32
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- FlexLED
- SilentPlus
- Activated charcoal filter saturation indicator
- Selectable fan setting: Über Schwadenschirm
- Telescopic casing: Standard
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Fleece grease filter: 2
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: included



Functions

- ComfortFix
- Extracted air
- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- SilentPlus
- FlexLED
- Cleaning lock
- Intensive setting
- Automatic after-running time

Additional data

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 28
- Illumination on cooking surface: 113 lux
- Grease absorption capacity rating: C
- Extracted air output, intensive setting: 765 m³/h
- Extracted air output, max. setting: 602 m³/h
- Extracted air output, min. setting: 247 m³/h
- Recirculation air output, intensive setting: 566 m³/h
- Recirculation air output, max. setting: 392 m³/h
- Recirculation air output, min. setting: 215 m³/h
- Extracted air noise output, intensive setting: 66 dB(A)
- Extracted air noise level, max. setting: 64 dB(A)
- Extracted air noise output, min. setting: 49 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1
- Motor output: 130 W
- Feature level: 5

Service and interfaces

- Warranty: 2 years