



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

## Brochure DF-SG 5/6



### **Selected product**

- Article no.: 6103160003
- EAN code: 7630029425251
- Controls: push buttons
- With pullout glass
- Standard width: 60 cm
- Front design: Stainless steel
- Installation method: built-in range hood



## Details DF SG6

### Design

- Controls: push buttons
- With pullout glass
- Standard width: 60 cm
- Front design: Stainless steel
- Installation method: built-in range hood

### Dimensions

- Niche width: 550 mm
- Max. niche width: 550 mm
- Niche depth: 280 mm
- Appliance height: 400 mm
- Front height: 46 mm
- Appliance width: 598 mm
- Appliance depth: 280 mm
- Max. appliance depth: 346 mm
- Empty weight: 16.5 kg

### Display and operation

- Controls: push buttons
- Fan power level display
- Lighting: LED
- Number of lights: 1

### Energy

- Energy efficiency rating: A
- Annual energy consumption: 44.9 kWh
- Lighting efficiency rating: B
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 1 x 7
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.21 kW
- Fuse protection (1): 10 A
- Plug type: Schuko 16A
- Connection cable: 1.5 m

### Range hood features

- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- With pullout glass
- Power levels: 3 + i
- Fleece grease filter: 1
- Non-return flap, integrated/attached: included

### Functions

- Extracted air
- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time

### Additional data

- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 0
- Illumination on cooking surface: 0 lux
- Grease absorption capacity rating: D
- Extracted air output, intensive setting: 625 m<sup>3</sup>/h
- Extracted air output, max. setting: 537 m<sup>3</sup>/h
- Extracted air output, min. setting: 240 m<sup>3</sup>/h
- Recirculation air output, intensive setting: 384 m<sup>3</sup>/h
- Recirculation air output, max. setting: 368 m<sup>3</sup>/h
- Recirculation air output, min. setting: 165 m<sup>3</sup>/h
- Extracted air noise output, intensive setting: 66 dB(A)
- Extracted air noise level, max. setting: 63 dB(A)
- Extracted air noise output, min. setting: 46 dB(A)
- Recirculation air noise output, intensive setting: 71 dB(A)
- Schalleistung Umluft max. Stufe: 69 dB(A)
- Recirculation air noise output, min. setting: 51 dB(A)
- Motor(s): 1
- Motor output: 200 W
- Feature level: 3



### **Preisschild Dunstabzüge**

- Extracted air
- Fleece grease filter: 1
- Grease filter cleaning indicator

### **Service and interfaces**

- Warranty: 2 years