



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

## Brochure Wall hood DWVHR9



Energy efficiency class

### Selected product

- Article no.: 6203000005 + H43400
- EAN code: 7630029438817 + 7630029409121
- Type: DWVHR9g
- Product category: Range hood
- Standard width: 90 cm
- Front design: Glass
- Installation method: Wall hood
- Recirculation air filter: Long-life activated charcoal filter



## Details Wall hood DWVHR9

### Additional settings

- Clean air function

### Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

### Design

- Type: DWVHR9g
- Product category: Range hood
- Standard width: 90 cm
- Front design: Glass
- Installation method: Wall hood
- Recirculation air filter: Long-life activated charcoal filter

### Dimensions

- Device height exhaust air: 805 mm
- Device height exhaust air maximum: 1435 mm
- Device height recirculation air: 500 mm
- Device height recirculation air maximum: 1435 mm
- Front height: 500 mm
- Appliance width: 898 mm
- Appliance depth: 338 mm
- Max. appliance depth: 338 mm
- Empty weight: 16 kg

### Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

### Energy

- Measurement and Calculation Method: EN61591
- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: A+
- Annual energy consumption: 39.9 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 34.8
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 1 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.27 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Connection cable: 1.5 m

### Range hood features

- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Dimming lights: 2-stage
- Grease filter: 1
- Side exhaust
- Non-return flap, integrated/attached: Included

### Functions

- Dimming lights: 2-stage
- Grease filter cleaning indicator
- Side exhaust
- Recirculation air
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time



#### **Additional data**

- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 91
- Illumination on cooking surface: 200 lux
- Grease absorption capacity rating: D
- Extracted air output, intensive setting: 750 m<sup>3</sup>/h
- Extracted air output, max. setting: 420 m<sup>3</sup>/h
- Extracted air output, min. setting: 270 m<sup>3</sup>/h
- Recirculation air output, intensive setting: 400 m<sup>3</sup>/h
- Recirculation air output, max. setting: 360 m<sup>3</sup>/h
- Recirculation air output, min. setting: 280 m<sup>3</sup>/h
- Extracted air noise output, intensive setting: 72 dB(A)
- Extracted air noise level, max. setting: 60 dB(A)
- Extracted air noise output, min. setting: 51 dB(A)
- Recirculation air noise output, intensive setting: 78 dB(A)
- Schalleistung Umluft max. Stufe: 76 dB(A)
- Recirculation air noise output, min. setting: 71 dB(A)
- Motor(s): 1
- Motor output: 270 W
- Feature level: 4

#### **Service and interfaces**

- Warranty: 2 years