



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

## Brochure AdoraWash V4000 OptiDos



Energy efficiency class



### Selected product

- Article no.: 1102310031
- EAN code: 7630029453544
- Type: AW4T-11023
- Product category: Washing machine
- Front design: White
- Door design: ChromeClass
- Door hinge: Right





## AdoraWash V4000 OptiDos

### Additional settings

- Degree of soiling / soaking
- Biological washing
- Soak
- Refinement
- Hygiene recommendation
- Quick wash / end of programme

### Compliant to regulation

- (EU) Nr. 2019/2017
- AS/NZS 2040.2:2012: No
- GB 12021.4-2013: No

### Design

- Type: AW4T-11023
- Product category: Washing machine
- Front design: White
- Door design: ChromeClass
- Door hinge: Right

### Dimensions

- Appliance height: 850 mm
- Max. appliance height: 870 mm
- Appliance height for built-under installation: 850 mm
- Appliance width: 595 mm
- Appliance depth: 625 mm
- Depth of appliance when door is open: 1059 mm
- Appliance depth including distance to wall: 638 mm
- Door opening angle: 180 °
- Pumping height for drain pump: 1.2 m
- Empty weight: 71 kg

### Display and operation

- Drum lighting
- Display: Full-colour graphic display, touchscreen
- Panel design: Acrylic glass
- Controls: TouchControl
- Remaining time display
- Number of languages in display: 9
- Languages in display: de, fr, it, rm, en, es, ru, tr, zh

### Energy

- Noise emission class: A
- Output - standby off: 0.15 W
- Output - standby on: 1.8 W
- Consumption when off: 0 W
- Automatic shut-off consumption with network switched on: 1 W
- Energy efficiency class: B
- Energy consumption per cycle in the "eco 40-60" programme: 0.54 kWh
- Weighted energy consumption for 100 cycles: 54 kWh
- Weighted water consumption per cycle: 43 l
- Energy efficiency index: 59.0
- Light sources must be replaced by a professional
- Light source regulations
- Spin drying efficiency class: B
- Type of connection (1): 220-240 V~
- Frequency (1): 50 Hz
- Connected loads (1): 2.3 kW
- Fuse protection (1): 10 A
- Plug type: BS1363/13A
- Connection cable: 1.8 m
- Water pressure: 1-10 bar





### **Washing machine features**

- Nominal capacity for the "eco 40-60" programme: 8.0 kg
- OptiDos
- Build: Front loader
- Premium Swiss Quality
- Free-standing appliance, stackable
- House type: Single-family home
- Nominal capacity: 8 kg
- Drum volume: 60 l
- EcoManagement
- OptiTime
- Pivoting operating panel
- Aquastop
- Partial load automatic energy saving
- Vibration Absorbing System (VAS)
- Turbidity sensor
- Automatic door opener
- Technology: Conventional

### **Nicht sichtbare Attribute**

- Eco programme

### **Functions**

- Favourites
- Steam anti-crease
- Fabric programmes
- Appliance hygiene
- AquaPlus
- Skin protection
- Sprint programme
- Wool
- Pre-wash
- Whites / coloureds 20 - 95°C
- Cold wash 20°C
- Hand wash 20°C
- Easy care
- Degree of soiling / Anti-mite
- Extra programmes
- Proofing
- Delayed start: 24 h
- Childproof lock





### **Additional data**

- Programme duration at half the nominal capacity ("eco 40-60"): 165.0 min
- Programme duration at nominal capacity ("eco 40-60"): 218.0 min
- Programme duration at one quarter of the nominal capacity ("eco 40-60"): 165.0 min
- (EU) No. 2019/2014 acoustic performance when spinning: 69.0 dB(A)
- (EU) No. 2019/2014 acoustic performance when washing: 48.0 dB(A)
- Washing efficiency index: 1.04
- IP Number: IPX4
- Spin speed at half the nominal capacity ("eco 40-60"): 1400.0 U/min
- Spin speed at nominal capacity ("eco 40-60"): 1400.0 U/min
- Spin speed at one quarter of the nominal capacity ("eco 40-60"): 1400.0 U/min
- Rinsing cycle in the "eco 40-60" programme: 4.5 g/kg
- Highest temperature within the textiles at half the nominal capacity ("eco 40-60"): 36.0 °C
- Highest temperature within the textiles at nominal capacity ("eco 40-60"): 37.0 °C
- Highest temperature within the textiles at one quarter of the nominal capacity ("eco 40-60"): 25.0 °C
- Maximum spin speed: 1600 U/min
- Spin speed: 400 U/min
- Noise output during spin phase: 69 dB(A)
- Noise output during washing phase: 49 dB(A)
- Fleet circulation
- Pressure hose G 3/4: 1.25 m
- Installation plate
- Drain hose: 1.5 m
- Feature level: 4

### **Service and interfaces**

- V-Upgrade compatible
- Frequency range: 2,4 GHz
- WLAN as standard: 802.11 b/g/n
- V-ZUG-Home
- Interface: WLAN and Bluetooth

