



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure AiroClearWall V6000



Energy efficiency class

Selected product

- Article no.: 6202900007 + 1046969
- EAN code: 7630029440292 + 7630029428979
- Type: AW6T12LQTLG
- Product category: Range hood
- Telescopic casing: Long
- Standard width: 120 cm
- Front design: Black glass
- Installation method: Wall hood
- Recirculation air filter: Longlife plus starter set



Details AiroClearWall V6000

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: AW6T12LQTLG
- Product category: Range hood
- Telescopic casing: Long
- Standard width: 120 cm
- Front design: Black glass
- Installation method: Wall hood
- Recirculation air filter: Longlife plus starter set

Dimensions

- Device height exhaust air: 660 mm
- Device height exhaust air maximum: 875 mm
- Device height recirculation air: 780 mm
- Device height recirculation air maximum: 995 mm
- Front height: 55 mm
- Appliance width: 1198 mm
- Appliance depth: 550 mm
- Max. appliance depth: 550 mm
- Empty weight: 29 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Measurement and Calculation Method: EN61591
- Output - standby off: 0.48 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: A+
- Annual energy consumption: 29.7 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 36.3
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 3 x 2 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.14 kW
- Fuse protection (1): 10 A
- Plug type: Schuko 16A
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- FlexLED
- SilentPlus
- Activated charcoal filter saturation indicator
- Telescopic casing: Long
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Grease filter: 4
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: Included



Functions

- OptiLink
- ComfortFix
- Grease filter cleaning indicator
- Recirculation air
- Activated charcoal filter saturation indicator
- SilentPlus
- FlexLED
- Cleaning lock
- Intensive setting
- Automatic after-running time

Additional data

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 33
- Illumination on cooking surface: 196 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 675 m³/h
- Extracted air output, max. setting: 452 m³/h
- Extracted air output, min. setting: 247 m³/h
- Recirculation air output, intensive setting: 570 m³/h
- Recirculation air output, max. setting: 389 m³/h
- Recirculation air output, min. setting: 210 m³/h
- Extracted air noise output, intensive setting: 63 dB(A)
- Extracted air noise level, max. setting: 52 dB(A)
- Extracted air noise output, min. setting: 38 dB(A)
- Recirculation air noise output, intensive setting: 68 dB(A)
- Schalleistung Umluft max. Stufe: 56 dB(A)
- Recirculation air noise output, min. setting: 41 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1
- Motor output: 130 W
- Feature level: 5

Service and interfaces

- Interface: Bluetooth