



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure DSTS9g



Energy efficiency class

Selected product

- Article no.: 6401500001
- EAN code: 7614816156139
- Product category: Range hood
- Type: DSTS9-64015
- Standard width: 90 cm
- Front design: Nero with glass
- Installation method: Downdraft



Details DSTS9g

Additional settings

- Clean air function

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Product category: Range hood
- Type: DSTS9-64015
- Standard width: 90 cm
- Front design: Nero with glass
- Installation method: Downdraft

Dimensions

- Appliance height: 650 mm
- Appliance width: 880 mm
- Appliance depth: 120 mm
- Max. appliance depth: 120 mm
- Declared weight: 35 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting technology: LED
- Number of light sources: 1

Environmental footprint

- Ecopoints end of life (EP): 762255
- Ecopoints device (EP): 294692
- Carbon footprint end of life (kg CO₂e): 267
- Carbon footprint device (kg CO₂e): 103
- Monetary equivalent end of life (CHF): 312
- Monetary equivalent device (CHF): 155

Energy

- Output - standby off: 0.49 W
- Light sources must be replaced by a professional
- Energy efficiency class: A
- Annual energy consumption: 56.9 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 29.3
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 1 x 5 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.276 kW
- Fuse protection (1): 10 A
- Plug type: Schuko 16A
- Plug type B: 1363/13A
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- Hood design: Downdraft
- LED candle: LED strip
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Dimming lights: 2-stage
- Grease filter: 2
- Side exhaust
- Non-return flap, integrated/attached: Included

Functions

- Extracted air
- Dimming lights: 2-stage
- Grease filter cleaning indicator
- Side exhaust
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time



Additional data

- Extracted air noise output, level 2: 49.0 dB(A)
- Extracted air noise output, level 3: 57.0 dB(A)
- Recirculation air noise output, level 2: 49.0 dB(A)
- Recirculation air noise output, level 3: 55.0 dB(A)
- Extracted air output, level 2: 280 m³/h
- Extracted air output, level 3: 440 m³/h
- Recirculation air output, level 2: 290 m³/h
- Recirculation air output, level 3: 440 m³/h
- Light colour in kelvin: 4000 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 40
- Illumination on cooking surface: 200 lux
- Grease absorption capacity rating: D
- Extracted air output, intensive setting: 720 m³/h
- Extracted air output, max. setting: 440 m³/h
- Extracted air output, min. setting: 200 m³/h
- Recirculation air output, intensive setting: 630 m³/h
- Recirculation air output, max. setting: 440 m³/h
- Recirculation air output, min. setting: 200 m³/h
- Extracted air noise output, intensive setting: 68 dB(A)
- Extracted air noise level, max. setting: 57 dB(A)
- Extracted air noise output, min. setting: 43 dB(A)
- Recirculation air noise output, intensive setting: 69 dB(A)
- Schalleistung Umluft max. Stufe: 55 dB(A)
- Recirculation air noise output, min. setting: 42 dB(A)
- Motor(s): 1
- Motor output: 270 W