



Data sheet AiroClearWall V6000

Article no.: 6202900007

Compliant to regulation (EU) Nr. 65/2014, (EU) Nr. 66/2014

Type: AW6T12LQTLG

Name	Unit	Value
Type		AW6T12LQTLG
Recirculation air noise output, min. setting	dB(A)	41
Schalleistung Umluft max. Stufe	dB(A)	56
Recirculation air noise output, intensive setting	dB(A)	68
ComfortFix		Yes
Consumption when off	W	0.0
(EU) Nr. 65/2014		Yes
(EU) Nr. 66/2014		Yes
Product category		Range hood
Annual energy consumption	kWh	29.7
Time increase factor		0.7
Fluid dynamic efficiency		36.3
Fluid dynamic efficiency rating		A
Energy efficiency index		40
Air output at best efficiency point	m ³ /h	371.7
Pressure capacity at best efficiency point	Pa	355
Extracted air output, min. setting	m ³ /h	247
Extracted air output, max. setting	m ³ /h	452
Extracted air output, intensive setting	m ³ /h	675
Electric power input at best efficiency point	W	100
Nominal lighting output (quantity x W)		3 x 2 W
Illumination on cooking surface	lx	196
Output - standby off	W	0.48
Extracted air noise output, min. setting	dB(A)	38
Extracted air noise level, max. setting	dB(A)	52



Extracted air noise output, intensive setting	dB(A)	63
Grease absorption capacity		89.5
Grease absorption capacity rating		B
Lighting efficiency		33
Lighting efficiency rating		A