



Data sheet AiroClearCabinet V6000

Article no.: V6105800006_Umluft_Longlife

Compliant to regulation (EU) Nr. 65/2014, (EU) Nr. 66/2014

Name	Unit	Value
Recirculation air noise output, min. setting	dB(A)	42
Schalleistung Umluft max. Stufe	dB(A)	57
Recirculation air noise output, intensive setting	dB(A)	68
ComfortFix		Yes
Consumption when off	W	0.0
(EU) Nr. 65/2014		Yes
(EU) Nr. 66/2014		Yes
Product category		Range hood
Annual energy consumption	kWh	31.2
Time increase factor		0.8
Fluid dynamic efficiency		34.7
Fluid dynamic efficiency rating		A
Energy efficiency index		42
Air output at best efficiency point	m ³ /h	380.59999999999917
Pressure capacity at best efficiency point	Pa	341
Extracted air output, min. setting	m ³ /h	247.00000000000034
Extracted air output, max. setting	m ³ /h	452.0000000000016
Extracted air output, intensive setting	m ³ /h	653.0000000000003
Electric power input at best efficiency point	W	103
Nominal lighting output (quantity x W)		2x2 W
Illumination on cooking surface	lx	113
Output - standby off	W	0.48
Extracted air noise output, min. setting	dB(A)	38
Extracted air noise level, max. setting	dB(A)	53
Extracted air noise output, intensive setting	dB(A)	64
Grease absorption capacity		82.0



Grease absorption capacity rating	C
Lighting efficiency	28
Lighting efficiency rating	A