



# Data sheet AiroClearWall V6000

Article no.: V6202900007\_Abluft

Compliant to regulation (EU) Nr. 65/2014, (EU) Nr. 66/2014

Name	Unit	Value
Recirculation air noise output, min. setting	dB(A)	41
Schalleistung Umluft max. Stufe	dB(A)	56
Recirculation air noise output, intensive setting	dB(A)	68
ComfortFix		Yes
Consumption when off	W	0.0
(EU) Nr. 65/2014		Yes
(EU) Nr. 66/2014		Yes
Product category		Range hood
Annual energy consumption	kWh	29.7
Time increase factor		0.7
Fluid dynamic efficiency		36.3
Fluid dynamic efficiency rating		A
Energy efficiency index		40
Air output at best efficiency point	m <sup>3</sup> /h	371.7
Pressure capacity at best efficiency point	Pa	355
Extracted air output, min. setting	m <sup>3</sup> /h	247.00000000000034
Extracted air output, max. setting	m <sup>3</sup> /h	452.0000000000016
Extracted air output, intensive setting	m <sup>3</sup> /h	675.0
Electric power input at best efficiency point	W	100
Nominal lighting output (quantity x W)		3x2W
Illumination on cooking surface	lx	196
Output - standby off	W	0.48
Extracted air noise output, min. setting	dB(A)	38
Extracted air noise level, max. setting	dB(A)	52
Extracted air noise output, intensive setting	dB(A)	63
Grease absorption capacity		89.5



Grease absorption capacity rating	B
Lighting efficiency	33
Lighting efficiency rating	A