



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure DSTS



Energy efficiency class

Selected product

- Article no.: 6400460005
- EAN code: 7630029417553
- Type: DSTS9g
- Product category: Range hood
- Standard width: 90 cm
- Front design: Glass
- Installation method: Downdraft



DSTS

Additional settings

- Clean air function

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: DSTS9g
- Product category: Range hood
- Standard width: 90 cm
- Front design: Glass
- Installation method: Downdraft

Dimensions

- Appliance height: 650 mm
- Appliance width: 880 mm
- Appliance depth: 120 mm
- Max. appliance depth: 120 mm
- Empty weight: 35 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 1

Energy

- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: B
- Annual energy consumption: 62.1 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 27.1
- Fluid dynamic efficiency rating: B
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 1 x 6 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.28 kW
- Fuse protection (1): 10 A
- Plug type: Schuko 16A
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Dimming lights: 2-stage
- Grease filter: 2
- Side exhaust
- Non-return flap, integrated/attached: Included

Functions

- Extracted air
- Dimming lights: 2-stage
- Grease filter cleaning indicator
- Side exhaust
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time



Additional data

- Light colour in kelvin: 4000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 28.1
- Illumination on cooking surface: 170 lux
- Grease absorption capacity rating: D
- Extracted air output, intensive setting: 670 m³/h
- Extracted air output, max. setting: 420 m³/h
- Extracted air output, min. setting: 280 m³/h
- Recirculation air output, intensive setting: 615 m³/h
- Recirculation air output, max. setting: 330 m³/h
- Recirculation air output, min. setting: 155 m³/h
- Extracted air noise output, intensive setting: 69 dB(A)
- Extracted air noise level, max. setting: 57 dB(A)
- Extracted air noise output, min. setting: 49 dB(A)
- Recirculation air noise output, intensive setting: 76 dB(A)
- Schalleistung Umluft max. Stufe: 60 dB(A)
- Recirculation air noise output, min. setting: 43 dB(A)
- Motor(s): 1
- Motor output: 270 W
- Feature level: 5

Service and interfaces

- Warranty: 2 years