



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure AiroClearCabinet V4000 with TwinBlower



Selected product

- Article no.: 6401100000
- EAN code: 7630029446799
- Type: AE4T-64011
- Product category: Range hood
- Standard width: 86 cm
- Front design: ChromeClass
- Installation method: Integrated range hood



AiroClearCabinet V4000 with TwinBlower

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: AE4T-64011
- Product category: Range hood
- Standard width: 86 cm
- Front design: ChromeClass
- Installation method: Integrated range hood

Dimensions

- Appliance height: 572 mm
- Front height: 6.5 mm
- Appliance width: 860 mm
- Appliance depth: 320 mm
- Max. appliance depth: 320 mm
- Empty weight: 27 kg

Display and operation

- Controls: Touch keys
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Output - standby off: 0.4 W
- Consumption when off: 0 W
- Energy efficiency class: C
- Annual energy consumption: 170.8 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 21.9
- Fluid dynamic efficiency rating: C
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 2 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.53 kW
- Fuse protection (1): 10 A
- Plug type: CH Typ 12
- Plug type B: AS/NZS 3112
- Plug type C: Schuko 16A
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- FlexLED
- SilentPlus
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Grease filter: 2
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: Included



Functions

- OptiLink
- ComfortFix
- Extracted air
- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- SilentPlus
- TwinBlower
- FlexLED
- Intensive setting
- Automatic after-running time

Additional data

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 200 mm
- Lighting efficiency: 42.2
- Illumination on cooking surface: 169 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 1230 m³/h
- Extracted air output, max. setting: 1162 m³/h
- Extracted air output, min. setting: 617 m³/h
- Extracted air noise output, intensive setting: 71 dB(A)
- Extracted air noise level, max. setting: 69 dB(A)
- Extracted air noise output, min. setting: 56 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 2
- Motor output: 530 W
- Feature level: 4

Service and interfaces

- Warranty: 2 + 8 years
- Warranty: 2 years
- Interface: Bluetooth