V-ZUG Ltd
Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland
Phone +41 58 767 67 67
info@vzug.com, www.vzug.com

# Brochure AiroClearIsland V6000

Energy efficiency class

**Selected product**

- Article no.: 6302000007
- EAN code: 7630029439678
- Type: AI6T12LQTLG
- Product category: Range hood
- Telescopic casing: Long
- Standard width: 120 cm
- Front design: Black glass
- Installation method: Island hood

# Details AiroClearIsland V6000

**Compliant to regulation**

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

**Design**

- Type: AI6T12LQTLG
- Product category: Range hood
- Telescopic casing: Long
- Standard width: 120 cm
- Front design: Black glass
- Installation method: Island hood

**Dimensions**

- Device height exhaust air: 640 mm
- Device height exhaust air maximum: 845 mm
- Device height recirculation air: 795 mm
- Device height recirculation air maximum: 1000 mm
- Front height: 55 mm
- Appliance width: 1200 mm
- Appliance depth: 700 mm
- Max. appliance depth: 700 mm
- Empty weight: 35 kg

**Display and operation**

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 4

**Energy**

- Output - standby off: 0.48 W
- Consumption when off: 0 W
- Light sources must be replaced by a professional
- Light source regulations
- Energy efficiency class: A+
- Annual energy consumption: 31.1 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 36.3
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 4 x 2 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.14 kW
- Fuse protection (1): 10 A
- Plug type: Schuko 16A
- Connection cable: 1.5 m

**Range hood features**

- Grease filter cleaning indicator
- FlexLED
- SilentPlus
- Activated charcoal filter saturation indicator
- Telescopic casing: Long
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Grease filter: 3
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: Included

**Functions**

- OptiLink
- ComfortFix
- Extracted air
- Grease filter cleaning indicator
- Activated charcoal filter saturation indicator
- SilentPlus
- FlexLED
- Cleaning lock
- Intensive setting
- Automatic after-running time

**Additional data**

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 28
- Illumination on cooking surface: 225 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 675 $m^3/h$
- Extracted air output, max. setting: 452 $m^3/h$
- Extracted air output, min. setting: 247 $m^3/h$
- Recirculation air output, intensive setting: 570 $m^3/h$
- Recirculation air output, max. setting: 389 $m^3/h$
- Recirculation air output, min. setting: 210 $m^3/h$
- Extracted air noise output, intensive setting: 63 dB(A)
- Extracted air noise level, max. setting: 52 dB(A)
- Extracted air noise output, min. setting: 38 dB(A)
- Recirculation air noise output, intensive setting: 68 dB(A)
- Schallleistung Umluft max. Stufe: 56 dB(A)
- Recirculation air noise output, min. setting: 41 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1
- Motor output: 130 W
- Feature level: 5

**Service and interfaces**

- Interface: Bluetooth